



OAK STUDIO AB OILED

Oak Studio AB Oiled is a small-sized strip parquet in a clean grading with moderate colour variations and few knots. Boxes contain left and right elements for herringbone installation.

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Product type / Construction	Wood Floors / 2-layer parquet	Moisture content	EN13183	7%±2%
Article Number / EAN Code	111PABEKFOKE050 / 7393969042055	Minimun Mean Density	>500 kg/m³	
Design / Wood Species	Herringbone / Oak	kg/m³		
Surface treatment / Natural/Stained	Oil / Natural	Reaction To Fire	EN13501-1	Cfl-s1
Width x Length x Thickness	70 x 490 x 11 mm	Formaldehyde Emission	EN717-1	E1
Weight per package / per m2	13 kg / 6.31 kg	Content PCP	CEN/TR14823	≤ 5 ppm
Area per package / per pallet	2.06 m² / 123.6 m²	Breaking Strength N/mm²	EN1533	NPD
Grading	Calm	Thermal Conductivity	EN12664	0,14 W/mK
Joint	Tongue & Groove	Thermal Resistance R-Value	.08 (m2K/W)	
Installation method	Glue-down	Biological Durability	EN350-2	Class 1
Floor heating	Yes	CARB2	Compliant	
Wear leayer material / thickness	Hardwood / 3.5 mm	Slip resistance	CEN/TS15676	NPD
Resandable	2 times			
Core material	Pine			
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9			
Warranty	30 years			

DETAILED DESCRIPTION
Even colour with minor variations.
Small sized knots in limited numbers allowed.
Oil: This floor should be oiled immediately after installation.
Colour change: Some muting of colour variation to medium, straw brown.
Packages may contain start and stop boards.

Other products in this collection



OAK STUDIO AB WHITE MATT



OAK STUDIO AB OILED



OAK STUDIO CD OILED



OAK STUDIO CD HB MATT



OAK STUDIO CC GREY



OAK STUDIO CD HB OILED



STUDIO OAK CC 11 MM



OAK STUDIO AB WHITE OILED



OAK STUDIO AB SMOKED



OAK STUDIO AB MATT