



7%±2% >500 kg/m³

Cfl-s1

≤ 5 x 10-6n NPD 0,14 W/mK .08 (m2K/W) Class 1 Compliant NPD

OAK STUDIO AB OILED

Oak Studio AB Oiled is a small-sized strip parquet in a clean grading with moderate colour variations and few knots. Boxes contain left and right elements for herringbone installation.

PRODUCT DETAILS		TECHNICAL PROPERTIES	
Product type / Construction	Wood Flooring / 2-layer parquet	Moisture content	EN13183
Article Number / EAN Code	111PABEKF0KE050 / 7393969042055	Minimun Mean Density	
Design / Wood Species	Herringbone / Oak	kg/m³	
Surface Treatment /	Oil / Natural	Reaction To Fire	EN13501-1
Natural/Stained		Formaldehyde Emission	EN717-1
Width x Length x Thickness	70 x 490 x 11 mm	Content PCP	CEN/TR14823
Weight per package / per	13 kg / 6.31 kg	Breaking Strength N/mm ²	EN1533
m2		Thermal Conductivity	EN12664
Area per package / per	2.06 m ² / 123.6 m ²	Thermal Resistance R-Value	
pallet		Biological Durability	EN350-2
Grading	Calm	CARB2	
Joint	Tongue & Groove	Slip resistance	CEN/TS15676
Installation method	Glue-down		
Floor heating	Yes		
Wear leayer material /	Hardwood / 3.5 mm		
thickness			
Core material	Pine		
Hardness (Brinell) value /	3,7 / 2.2 - 5.9		
range			
Warranty	30 years		

TECHNICAL PROPERTIES

DETAILED DESCRIPTION

Even colour with minor variations.

Small sized knots in limited numbers allowed

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Other products in this collection

