



7%±2%

Cfl-s1

E1

NPD 0,14 W/mK

 $>500 \text{ kg/m}^3$

≤ 5 x 10-6n

.08 (m2K/W)

Class 1 Compliant NPD

EN13183

EN13501-1

CEN/TR14823

EN717-1

EN1533

EN12664

EN350-2

CEN/TS15676

OAK STUDIO AB OILED

Oak Studio AB Oiled is a small-sized strip parquet in a clean grading with moderate colour variations and few knots. Boxes contain left and right elements for herringbone installation.

PRODUCT DETAILS		TECHNICAL PROPERTIES
Product type / Construction	Wood Flooring / 2-layer parquet	Moisture content
Article Number / EAN Code	111PABEKF0KE050 / 7393969042055	Minimun Mean Density
Design / Wood Species	Pattern / Oak	kg/m³
Surface Treatment /	Oil / Natural	Reaction To Fire
Natural/Stained		Formaldehyde Emission
Width x Length x Thickness	70 x 490 x 11 mm	Content PCP
Weight per package / per	13 kg / 6.31 kg	Breaking Strength N/mm ²
m2		Thermal Conductivity
Area per package / per	2.06 m ² / 123.6 m ²	Thermal Resistance R-Value
pallet		Biological Durability
Grading	Calm	CARB2
Joint	Tongue & Groove	Slip resistance
Installation method	Glue-down	
Floor heating	Yes	<u></u>
Wear leayer material /	Hardwood / 4 mm	
thickness		<u></u>
Core material	Pine lamella	
Brinell value / range	3,7 / 2.2 - 5.9	<u></u>
Warranty	30 years	

TECHNICAL PROPERTIES

DETAILED DESCRIPTION

Even colour with minor variations.

Small sized knots in limited numbers allowed.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Other products in this collection







Studio Oak AB White 11 mm



Oak Studio AB Smoked



Oak Studio AB



Oak Studio CD