



## OAK BURGUNDY

This single-strip oak floor from the European Naturals Collection features hayseed brown hues highlighted with darker, natural grain design. Four-sided microbevelling at the edges ensures a classic, full plank look and feel. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer parquet	
Article Number / EAN Code	151N8AEKF0KW220 / 7393969041256	
Design / Wood Species	1-strip / Oak	
Surface treatment /	Oil / Natural	
Natural/Stained		
Design features	Microbevelled 4-sided, Brushed	
Width x Length x Thickness	187 x 2266 x 15 mm	
Weight per package / per	21 kg / 8.4 kg	
m2		
Area per package	2.5 m <sup>2</sup>	
Area per package Grading	2.5 m <sup>2</sup> Lively	
Grading	Lively	
Grading Joint	Lively Woodloc® 5S	
Grading Joint Installation method	Lively Woodloc® 5S Floating, Glue-down	
Grading Joint Installation method Floor heating	Lively Woodloc® 5S Floating, Glue-down Yes	
Grading Joint Installation method Floor heating Wear leayer material /	Lively Woodloc® 5S Floating, Glue-down Yes	
Grading Joint Installation method Floor heating Wear leayer material / thickness	Lively Woodloc® 5S Floating, Glue-down Yes Hardwood / 3.5 mm	
Grading Joint Installation method Floor heating Wear leayer material / thickness Resandable	Lively Woodloc® 5S Floating, Glue-down Yes Hardwood / 3.5 mm	

## PRODUCT DETAILS

Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	2	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



















## DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown.

The product includes large sound and black knots. Knots may vary in size and numbers.

Oil: This floor should be oiled immediately after installation.

**Colour change**: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

## Other products in this collection



Oak Ardenne



Oak Starnberg



Oak Rochford



Oak Burgundy





Oak Siena



Oak Hampshire



Oak Cornwall



Oak Como