



# OAK BURGUNDY

Oak Burgundy is a classic floor, where the natural wood characteristics has been enhanced with microbevel and brushing topped with a natural oil.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	151N8AEKF0KW220	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969041256	Design	1-strip	Minimum Mean Density kg/m³ >500 kg/m³		
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Lively			
Refining Treatment	Microbevelled 4-sided, Brushed	Range	Kährs Original	Reaction To Fire	EN13501-1	Dfl-s1
		Collection	European Naturals Collection	Formaldehyde Emission	EN717-1	E1
Dimensions	187 x 2266 mm	Natural/Stained	Natural	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Weight per Package	21 kg	Brinell Value	3,7	Breaking Strength N/mm²	EN1533	NPD
Area per Package	2.5 m²	Joint	Woodloc® 5S	Thermal Conductivity	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Floor heating	Yes	Thermal Resistance R-Value		.11 (m2K/W)
DETAIL DESCRIPTION		Wear-layer material	Hardwood	Biological Durability	EN350-2	Class 1
		Wear Layer Thickness	3.5 mm	CARB2		Compliant
		Core material	Pine/Spruce lamella	Slipperiness	CEN/TS15676	NPD
			15 mm			
		Installation method	Floating, Glue-down			

## COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

Other products in this collection



Oak Burgundy



Oak Verona



Oak Siena



Oak Hampshire



Oak Cornwall

CERTIFICATES



Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*