



OAK VILLAGE

Oak Village is a brushed oiled rustic floor with cracks and knots that enhance the natural wood feeling.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	37107AEKF0KW180	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969106924	Design	1-strip	Minimum Mean Density kg/m³ >800 kg/m³		
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Dynamic	Reaction To Fire	EN13501-1	Cfl-s1
Refining Treatment	Microbevelled 4-sided, Brushed	Range	Kährs Linnea	Formaldehyde Emission	EN717-1	E1
Dimensions	150 x 1810 mm	Collection	Habitat Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Weight per Package	20 kg	Natural/Stained	Natural	Breaking Strength N/mm²	EN1533	NPD
Area per Package	3.3 m²	Brinell Value	5 - 6	Thermal Conductivity	EN12664	0,22 W/mK
Package info	Packages may contain start and stop boards.	Joint	Woodloc®	Thermal Resistance R-Value		.031 (m2K/W)
DETAIL DESCRIPTION		Floor heating	Yes	Biological Durability	EN350-2	Class 1
		Wear-layer material	Hardwood	CARB2		Compliant
		Wear Layer Thickness	0.6 mm	Slipperiness	CEN/TS15676	NPD
		Core material	HDF			
			7 mm			
		Installation method	Floating, Glue-down			

COLOUR CHANGE

Some muting of colour variation to medium, straw brown.



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.