



OAK FREDRIK

DDODLICT DETAIL C

The beige-brown hues in this single-strip floor from the Founders Collection are accentuated by its rich smoked finish, resulting in a warm, rustic expression. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /
Article Number / EAN Code	151N7BEKFCKW240 / 7393969036047	range
Design / Wood Species	1-strip / Oak	Warranty
Surface treatment /	Oil / Natural	TECHNICAL PROPERTIE
Natural/Stained		— Moisture content
Design features	Bevelled 4-sided, Handscraped, Brushed,	Minimun Mean Density
	Smoked	— kg/m ³
Width x Length x Thickness	187 x 2420 x 15 mm	— Reaction To Fire
Weight per package / per	22 kg / 8.15 kg	
m2		Formaldehyde Emission
Area per package / per	2.72 m ² / 122.4 m ²	Content PCP
pallet		Breaking Strength N/mm ²
<u> </u>	D	— Thermal Conductivity
Grading	Dynamic	Biological Durability
Joint	Woodloc® 5S	— CARB2
Installation method	Floating, Glue-down	
Floor heating	Yes	Slip resistance
Wear leayer material /	Hardwood / 3.5 mm	TSCA SONAN ESCA
thickness		CARB P2
Resandable	2-3 times	Compliant
Core material	Pine/Spruce lamella	floor CC
Backside material	HardwoodHardwood	Occupied C

PRODUCT DETAILS

	-/			
range				
Warranty 30 years				
TECHNICAL PROPERTIES				
- Moisture content	EN13183			
Minimun Mean Density				

Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

3.7 / 2.2 - 5.9













7%±2%







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

