



OAK FREDRIK

The beige-brown hues in this single-strip floor from the Founders Collection are accentuated by its rich smoked finish, resulting in a warm, rustic expression. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /
Article Number / EAN Code	151N7BEKFCKW240 / 7393969036047	range
Design / Wood Species	1-strip / Oak	Warranty
Surface treatment /	Oil / Natural	TECHNICAL PROPERTIE
Natural/Stained		Moisture content
Design features	Bevelled 4-sided, Handscraped, Brushed,	Minimun Mean Density
	Smoked	— kg/m ³
Width x Length x Thickness	187 x 2420 x 15 mm	— Reaction To Fire
Weight per package / per	22 kg / 8.15 kg	
m2		Formaldehyde Emission
Area per package / per	2.7 m ² / 122.4 m ²	Content PCP
	2.7 111 7 122.1 111	Breaking Strength N/mm ²
pallet		— Thermal Conductivity
Grading	Dynamic	Thermal Resistance R-Valu
Joint	Woodloc® 5S	Biological Durability
Installation method	Floating, Glue-down	— CARB2
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	Slip resistance
thickness		TSCA SCENANCO
Resandable	2-3 times	CARB P2
Core material	Pine/Spruce lamella	Compliant
Backside material	HardwoodHardwood	floor
	-	33010.

PRODUCT DETAILS

range		
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Resistance R-Value	!	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CFN/TS15676	NPD

3.7 / 2.2 - 5.9



















DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

Other products in this collection





OAK STURE

OAK GUSTAF