



OAK FREDRIK

PRODUCT DETAILS

The beige-brown hues in this single-strip floor from the Founders Collection are accentuated by its rich smoked finish, resulting in a warm, rustic expression. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

INODUCT DETAILS		I NODOCI DEIAILS	
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /	
Article Number / EAN Code	151N7BEKFCKW240 / 7393969036047	range	
Design / Wood Species	Plank / Oak	Warranty	
Surface treatment /	Oil / Natural	TECHNICAL PROPERTIE	
Natural/Stained		— Moisture content	
Design features	Bevelled 4-sided, Handscraped, Brushed,	Minimun Mean Density	
	Smoked	— kg/m ³	
Width x Length x Thickness	187 x 2420 x 15 mm	— Reaction To Fire	
Weight per package / per	22 kg / 8.15 kg	Formaldehyde Emission	
m2			
Area per package / per	2.72 m ² / 122.4 m ²	Content PCP	
pallet		Breaking Strength N/mm ²	
Grading	Dynamic	Thermal Conductivity	
	,	— Biological Durability	
Joint	Woodloc® 5S	— CARB2	
Installation method	Floating, Glue-down	— Slip resistance	
Floor heating	Yes	Jilp resistance	
Wear leayer material /	Hardwood / 3.5 mm	TSCA SONAN COLUMN TITLE VI	
thickness		CARB P2	
Resandable	2-3 times	Compliant	
Core material	Pine/Spruce	floor CC	
Backside material	HardwoodHardwood	G (COTTON OF THE COTTON OT THE COTTON OT THE COTTON OT THE COTTON OT THE	

PRODUCT DETAILS

range		
Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK

3.7 / 2.2 - 5.9









CEN/TS15676

EN350-2





Class 1

NPD

Compliant







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

