



OAK FREDRIK

The beige-brown hues in this single-strip floor from the Founders Collection are accentuated by its rich smoked finish, resulting in a warm, rustic expression. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

| PRODUCT DETAILS | | PRODUCT DETAIL |
|-----------------------------|---|------------------------------|
| Product type / Construction | Wood Flooring / 3-layer parquet | Brinell value / range |
| Article Number / EAN Code | 151N7BEKFCKW240 / 7393969036047 | Warranty |
| Design / Wood Species | 1-strip / Oak | TECHNICAL PROP |
| Surface treatment / | Oil / Natural | Moisture content |
| Natural/Stained | | |
| Design features | Bevelled 4-sided, Handscraped, Brushed, | — Minimun Mean Dens kg/m³ |
| | Smoked | - |
| Width x Length x Thickness | 187 x 2420 x 15 mm | Reaction To Fire |
| Weight per package / per | 22 kg / 8.15 kg | Formaldehyde Emiss |
| m2 | 22 16 / 0.13 16 | Content PCP |
| | 2.7 m ² / 122.4 m ² | Breaking Strength Na |
| Area per package / per | 2.7 111-7 122.4 111- | Thermal Conductivity |
| pallet | | Thermal Resistance I |
| Grading | Dynamic | Biological Durability |
| Joint | Woodloc® 5S | |
| Installation method | Floating, Glue-down | — CARB2 |
| Floor heating | Yes | Slip resistance |
| Wear leayer material / | Hardwood / 3.5 mm | TSCA SC SWAN ECO. |
| thickness | | CARB P2 |
| Resandable | 2-3 times | Compliant |
| Core material | Pine/Spruce lamella | sfloor C C |
| Backside material | HardwoodHardwood | O SCI OTTO |
| | | |

PRODUCT DETAILS

| Brinell value / range | 3,7 / 2.2 - 5.9 | |
|----------------------------|-----------------|-------------|
| Warranty | 30 years | |
| TECHNICAL PROPERTIES | 5 | |
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m³ |
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | 2 | .11 (m2K/W) |









CEN/TS15676

EN350-2





NPD

Class 1

Compliant







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

Other products in this collection









Oak Sture Oak Ulf

Oak Gustaf Oak Fredrik