



# OAK FREDRIK

The beige-brown hues in this single-strip floor from the Founders Collection are accentuated by its rich smoked finish, resulting in a warm, rustic expression. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS	
Article Number	151N7BEKFKW240
EAN Code	7393969036047
Surface treatment	Oil This floor should be oiled immediately after installation.
Design features	Bevelled 4-sided, Handscraped, Brushed, Smoked
Dimensions	187 x 2420 mm
Weight per Package	22 kg
Area per Package	2.7 m²
Area per pallet	122.4 m²
Package info	Packages may contain start and stop boards.

DETAIL DESCRIPTION
All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occurring wood color variations and create further contrast between light and dark. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE
Smoked product - noticeable color change over time.

FACTS	
Wood Species	Oak
Design	1-strip
Grading	Dynamic
Range	Kährs Original
Collection	Founders Collection
Resandable	2-3 times
Natural/Stained	Natural
Brinell Value	3,7
Joint	Woodloc® 5S
Floor heating	Yes
Warranty	30 years
Warranty US	25 years
Wear-layer material	Hardwood
Wear Layer Thickness	3.5 mm
Core material	Pine/Spruce lamella
Backside material	HardwoodHardwood
Thickness	15 mm
Installation method	Floating, Glue-down
Surface Colour	Dark Brown FC

TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³	>500 kg/m³	
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	.11 (m2K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slipperiness	CEN/TS15676	NPD

Other products in this collection



Oak Sture



Oak Ulf



Oak Gustaf



Oak Fredrik

CERTIFICATES



Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*