



Founders Collection

Kährs



OAK STURE

The natural oil stain on this single-strip oak floor from the Founders Collection accentuates the lightly smoked finish, resulting in a subtle, rustic expression. Every board is carefully brushed to bring out the character of the grain and highlight the texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS

| | |
|---|--|
| Product type / Construction | Wood Flooring / 3-layer parquet |
| Article Number / EAN Code | 151N7BEKFMKW240 / 7393969036054 |
| Design / Wood Species | 1-strip / Oak |
| Surface treatment / Natural/Stained | Oil / Stained |
| Design features | Bevelled 4-sided, Handscraped, Brushed, Light smoked |
| Width x Length x Thickness | 187 x 2420 x 15 mm |
| Weight per package / per m ² | 22 kg / 8.15 kg |
| Area per package / per pallet | 2.7 m ² / 122.4 m ² |
| Grading | Dynamic |
| Joint | Woodloc® 5S |
| Installation method | Glue-down, Floating |
| Floor heating | Yes |
| Wear layer material / thickness | Hardwood / 3.5 mm |
| Resandable | 2-3 times |
| Core material | Pine/Spruce lamella |
| Brinell value / range | 3,7 / 2.2 - 5.9 |

PRODUCT DETAILS

| | |
|----------|----------|
| Warranty | 30 years |
|----------|----------|

TECHNICAL PROPERTIES

| | | |
|-------------------------------------|-------------|--------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density | | >500 kg/m ³ |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | | .11 (m ² K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.


Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2024-07-27

Other products in this collection



Oak Sture



Oak Ulf



Oak Gustaf



Oak Fredrik