



OAK ULF

DDODLICT DETAIL C

The dark brown tones in this single-strip oak floor from the Founders Collection are enriched by a beautifully smoked finish, resulting in a warm, dark grey stain punctuated by charcoal knots and cracks. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer engineered
Article Number / EAN Code	151N7BEKFBKW240 / 7393969036030
Design / Wood Species	1-strip / White Oak
Surface Treatment /	Oil / Stained
Natural/Stained	
Refining Treatment	Beveled 4-sided, Handscraped, Brushed
Width x Length x Thickness	7 3/8 x 95 1/4 x 5/8"
Weight per package / per	48.5 lbs / 18 lbs
m2	
Area per package / per	29.3 sqft / 1317.5 sqft
pallet	
Grading	Dynamic
Joint	Woodloc® 5S
Installation method	Glue-Down, Floating
Floor heating	Yes
Wear leayer material /	Hardwood / 1/8"
thickness	
Resandable	2 times
Core material	Pine/Spruce
Hardness (Brinell) value /	3,7 / 2.2 - 5.9
range	

000	LICT	DETAIL	_
PROD	UCI	DETAIL	_S

Warranty	25 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD









DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

