



NPD

Class 1

.11 (m2K/W)

Compliant NPD

OAK GUSTAF

Oak Gustaf is a true rustic product where the surface is handcrafted and deeply brushed to enhance the beauty and specific characteristics of each and every board. A white stain gives the floor a muted white look. Nature oil finished.

PRODUCT DETAILS

Breaking Strength N/mm²

Biological Durability

Thermal Resistance R-Value

Warranty

PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer parquet	
Article Number / EAN Code	151N7BEKFVKW240 / 7393969036061	
Design / Wood Species	1-strip / Oak	
Surface Treatment /	Oil / Stained	
Natural/Stained		
Refining Treatment	Bevelled 4-sided, Handscraped, Brushed	
Width x Length x Thickness	187 x 2420 x 15 mm	
Weight per package / per	22 kg / 8.15 kg	
m2		
Area per package / per	2.7 m ² / 122.4 m ²	
pallet		
Grading	Dynamic	
Joint	Woodloc® 5S	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	
thickness		
Resandable	2-3 times	
Core material	Pine/Spruce lamella	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

)	
TECHNICAL PROPERTIE	S	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n

30 years



Slip resistance

CARB2







CEN/TS15676

EN1533

EN350-2

DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection





OAK STURE

OAK GUSTAF