



OAK GUSTAF

Oak Gustaf is a true rustic product where the surface is handcrafted and deeply brushed to enhance the beauty and specific characteristics of each and every board. A white stain gives the floor a muted white look. Nature oil finished.

PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	151N7BEKFVKW240 / 7393969036061
Design / Wood Species	1-strip / Oak
Surface Treatment /	Oil / Stained
Natural/Stained	
Refining Treatment	Bevelled 4-sided, Handscraped, Brushed
Width x Length x Thickness	187 x 2420 x 15 mm
Weight per package / per	22 kg / 8.15 kg
<u>m2</u>	
Area per package / per	2.7 m ² / 122.4 m ²
pallet	
Grading	Dynamic
Joint	Woodloc® 5S
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 3.5 mm
thickness	
Resandable	2-3 times
Core material	Pine/Spruce lamella
Brinell value / range	3,7 / 2.2 - 5.9

P	RO	DI	JC	Τ	DE	: T/	41	LS

Warranty	30 years	
TECHNICAL PROPERTIES		
- Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
- kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
- Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
- Slip resistance	CEN/TS15676	NPD









DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection









Oak Sture Oak Ulf

Oak Gustaf Oak Fredrik