



## **OAK GUSTAF**

Oak Gustaf is a true rustic product where the surface is handcrafted and deeply brushed to enhance the beauty and specific characteristics of each and every board. A white stain gives the floor a muted white look. Nature oil finished. This product must be oiled after installation and prior to use.

PRODUCT DETAILS		
Construction	3-layer engineered	
Article Number / EAN Code	151N7BEKFVKW240 / 7393969036061	
Design / Wood Species	1-strip / White Oak	
Surface Treatment /	Oil / Stained	
Natural/Stained		
Refining Treatment	Beveled 4-sided, Handscraped, Brushed	
Width x Length x Thickness	7 3/8 x 95 1/4 x 5/8"	
Weight per package / per	48.5 lbs / 18 lbs	
m2		
Area per package / per	29.1 sqft / 1317.5 sqft	
pallet		
Grading	Dynamic	
Joint	Woodloc® 5S	
Installation method	Floating, Glue-Down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 1/8"	
thickness		
Resandable	2 times	
Core material	Pine/Spruce lamella	
Brinell value / range	3,7 / 2.2 - 5.9	

PRODUCT DETAILS	S
-----------------	---

Warranty	25 years	
TECHNICAL PROPERTIES	;	
- Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD











## DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

**Oil:** This floor should be oiled immediately after installation.

**Colour change**: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## Other products in this collection









Oak Sture Oak Ulf

Oak Gustaf Oak Fredrik