



ATELIER OAK AB WHITE 11 MM

Oak AB White, a 2-layer construction, is an oak floor with colour variations and small knots. Offered with a variety of surface treatments and patterns.

PRODUCT DETAILS

Product type / Construction	Wood Floors / 2-layer parquet
Article Number / EAN Code	111PABEKFVKE120 / 7393969042277
Design / Wood Species	1-strip / Oak
Surface treatment / Natural/Stained	Oil / Stained
Design features	Brushed, Microbevelled 4-sided
Width x Length x Thickness	120 x 1200 x 11 mm
Weight per package / per m2	9.4 kg / 6.71 kg
Area per package	1.4 m ²
Grading	Variation
Joint	Tongue & Groove
Installation method	Glue-down
Floor heating	Yes
Wear layer material / thickness	Hardwood / 3.5 mm
Resandable	2 times
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
Warranty	30 years

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density		>500 kg/m ³
Reaction To Fire	EN13501-1	Cfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,17W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

DETAILED DESCRIPTION

Mainly laying year rings with colour variation, sapwood allowed up to 35% of the surface. Knots up to 5 mm.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - little colour change.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

www.kahrs.com | ©Kährs

2025-07-02

