



## WALNUT GEORGIA

Walnut Georgia is a dark, brushed floor in a natural, lively grade.

| PRODUCT DETAILS             |                                 |  |
|-----------------------------|---------------------------------|--|
| Product type / Construction | Wood Flooring / 3-layer parquet |  |
| Article Number / EAN Code   | 152N8EVAF0KW240 / 7393969035774 |  |
| Design / Wood Species       | 2-strip / Walnut                |  |
| Surface Treatment /         | Oil / Natural                   |  |
| Natural/Stained             |                                 |  |
| Refining Treatment          | Brushed                         |  |
| Width x Length x Thickness  | 200 x 2421 x 15 mm              |  |
| Weight per package / per    | 23 kg / 7.93 kg                 |  |
| m2                          |                                 |  |
| Area per package            | 2.9 m <sup>2</sup>              |  |
| Grading                     | Lively                          |  |
| Joint                       | Woodloc® 5S                     |  |
| Installation method         | Floating, Glue-down             |  |
| Floor heating               | Yes                             |  |
| Wear leayer material /      | Hardwood / 3.5 mm               |  |
| thickness                   |                                 |  |
| Resandable                  | 2-3 times                       |  |
| Core material               | Pine/Spruce lamella             |  |
| Hardness (Brinell) value /  | 3,4 / 2.0 - 5.1                 |  |
| range                       |                                 |  |

## PRODUCT DETAILS

| Warranty                            | 30 years    |             |
|-------------------------------------|-------------|-------------|
| TECHNICAL PROPERTIES                | 5           |             |
| Moisture content                    | EN13183     | 7%±2%       |
| Minimun Mean Density                |             | >500 kg/m³  |
| kg/m³                               |             |             |
| Reaction To Fire                    | EN13501-1   | Dfl-s1      |
| Formaldehyde Emission               | EN717-1     | E1          |
| Content PCP                         | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD         |
| Thermal Resistance R-Value          | 2           | .11 (m2K/W) |
| Biological Durability               | EN350-2     | Class 1     |
| CARB2                               |             | Compliant   |
| Slip resistance                     | CEN/TS15676 | NPD         |









## DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes large sound and black knots. Knots may vary in size and numbers.

Oil: This floor should be oiled immediately after installation.

**Colour change**: Changes to golden brown.

Packages may contain start and stop boards.

