



## OAK CHATEAU

Chateau is an extremely rustic board with knots and cracks. This product must be oiled after installation and prior to use.

PRODUCT DETAILS		TECHNICAL PROPERTIES
Product type / Construction	Wood Flooring / 3-layer parquet	Moisture content
Article Number / EAN Code	201XDDEKF0KE280 / 7393969035194	Minimun Mean Density
Design / Wood Species	1-strip / Oak	kg/m³
Surface Treatment /	Oil / Natural	Reaction To Fire
Natural/Stained		Formaldehyde Emission
Refining Treatment	Bevelled 4-sided, Brushed	Content PCP
Width x Length x Thickness	260 x 2800 x 20 mm	Breaking Strength N/mm <sup>2</sup>
Weight per package / per	38 kg / 13.1 kg	Thermal Conductivity
m2		Thermal Resistance R-Value
Area per package	2.9 m <sup>2</sup>	Biological Durability
Grading	Dynamic	CARB2
Joint	Tongue & Groove	Slip resistance
Installation method	Glue-down	SION CO
Floor heating	No	
Wear leayer material /	Hardwood / 5 mm	AND AND STANDARD
thickness		
Backside material	Veneer	
Warranty	30 years	

TECHNICAL PROPERTIES	)	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,125 W/mK
Thermal Resistance R-Value		.16 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD





## TECHNICAL PROPERTIES

## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. Grande products may continue to develop their rustic nature after the floor has been installed; splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

