



## OAK JOHAN

Oak Johan is a true rustic product where the surface is handcrafted and deeply brushed to enhance the beauty and specific characteristics of each and every board. Nature oil finished.

PRODUCT DETAILS

	PRODUCT DE
Wood Flooring / 3-layer parquet	Warranty
151N7BEKF0KW240 / 7393969036023	— TECHNICAL P
1-strip / Oak	Moisture conte
Oil / Natural	Minimun Mean
Bevelled 4-sided, Handscraped, Brushed	<ul> <li>kg/m³</li> <li>Reaction To Fire</li> </ul>
187 x 2420 x 15 mm	Formaldehyde
22 kg / 8.15 kg	Content PCP
	-
2.7 m <sup>2</sup> / 122.4 m <sup>2</sup>	Breaking Streng  The arread Basista
	Thermal Resista
Dynamic	Biological Dural
Woodloc® 5S	— CARB2
Floating, Glue-down	Slip resistance
Yes	GMSSION CLASS SPREAMOND CANA
Hardwood / 3.5 mm	:M1>; [
	STAM OH
2-3 times	<del></del>
Pine/Spruce lamella	<del></del>
3,7 / 2.2 - 5.9	
	<u></u>
	151N7BEKF0KW240 / 7393969036023  1-strip / Oak Oil / Natural  Bevelled 4-sided, Handscraped, Brushed 187 x 2420 x 15 mm 22 kg / 8.15 kg  2.7 m² / 122.4 m²  Dynamic  Woodloc® 5S Floating, Glue-down Yes Hardwood / 3.5 mm  2-3 times Pine/Spruce lamella

Warrar	nty	30 years	
— TECHI	NICAL PROPERTIES		
— Moistu	ire content	EN13183	7%±2%
Minim	un Mean Density		>500 kg/m³
— kg/m³			
- Reaction	on To Fire	EN13501-1	Dfl-s1
Forma	ldehyde Emission	EN717-1	E1
Conter	nt PCP	CEN/TR14823	≤ 5 x 10-6n
Breaki	ng Strength N/mm²	EN1533	NPD
Therm	al Resistance R-Value		.11 (m2K/W)
— Biologi	cal Durability	EN350-2	Class 1









CEN/TS15676

## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Compliant

NPD

## Other products in this collection





OAK STURE

OAK GUSTAF