



## OAK CHALET

DDODUCT DETAIL O

The white oil on this single-strip oak floor from the Grande Collection tempers the richness of the wood, balancing the burnished and smoky tones in the timber. The naturally occurring knots and cracks bring added depth to its surface and age the floor for a well-worn and rustic expression. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the appearance of the floor. This product must be oiled after installation and prior to use.

PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	
Article Number / EAN Code	201XDDEKFVKE280 / 7393969036641	
Design / Wood Species	1-strip / Oak	
Surface treatment /	Oil / Stained	
Natural/Stained		
Design features	Bevelled 4-sided, Brushed, Smoked,	
	Handscraped	
Width x Length x Thickness	260 x 2800 x 20 mm	
Weight per package / per	38 kg / 13.1 kg	
m2		
Area per package	2.9 m <sup>2</sup>	
Grading	Dynamic	
Joint	Tongue & Groove	
Installation method	Glue-down	
Floor heating	No	
Wear leayer material /	Hardwood / 5 mm	
thickness		
Resandable	2-4 times	
Backside material	Veneer	
Warranty	30 years	

## **TECHNICAL PROPERTIES**

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,125 W/mK
Thermal Resistance R-Value	2	.16 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD









## DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. Grande products may continue to develop their rustic nature after the floor has been installed; splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

**Descriptions & Imagery** 

www.kahrs.com | ©Kährs

