



CHALET OAK

The white oil on this single-strip oak floor from the Grande Collection tempers the richness of the wood, balancing the burnished and smoky tones in the timber. The naturally occurring knots and cracks bring added depth to its surface and age the floor for a well-worn and rustic expression. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the appearance of the floor. This product must be oiled after installation and prior to use.

PRODUCT DETAILS	
Article Number	201XDDEKFVKE280
EAN Code	7393969036641
Surface treatment	Oil This floor should be oiled immediately after installation.
Design features	Bevelled 4-sided, Brushed, Smoked, Handscraped
Dimensions	260 x 2800 mm
Weight per Package	38 kg
Area per Package	2.9 m ²
Package info	Packages may contain start and stop boards.

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. Grande products may continue to develop their rustic nature after the floor has been installed, splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.

COLOUR CHANGE

Smoked product - noticable color change over time.

FACTS	
Wood Species	Oak
Design	1-strip
Grading	Dynamic
Range	Kährs Supreme
Collection	Grande Collection
Resandable	2-4 times
Natural/Stained	Stained
Joint	Tongue & Groove
Floor heating	No
Warranty	30 years
Wear-layer material	Hardwood
Wear Layer Thickness	5 mm
Backside material	Veneer
Thickness	20 mm
Installation method	Glue-down
Surface Colour	Dark White

TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density kg/m ³	>500 kg/m ³	
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,125 W/mK
Thermal Resistance R-Value	.16 (m2K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slipperiness	CEN/TS15676	NPD

Other products in this collection



Manor Oak

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.