

OAK CHALET

The white oil on this single-strip oak floor from the Grande Collection tempers the richness of the wood, balancing the burnished and smoky tones in the timber. The naturally occurring knots and cracks bring added depth to its surface and age the floor for a well-worn and rustic expression. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the appearance of the floor. This product must be oiled after installation and prior to use.

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Product type / Construction	Wood Flooring / 3-layer parquet	Moisture content	EN13183	7%±2%
Article Number / EAN Code	201XDDEKFVKE280 / 7393969036641	Minimun Mean Density		>500 kg/m³
Design / Wood Species	1-strip / Oak	kg/m ³		
Surface Treatment /	Oil / Stained	Reaction To Fire	EN13501-1	Dfl-s1
Natural/Stained		Formaldehyde Emission	EN717-1	E1
Refining Treatment	Bevelled 4-sided, Brushed, Smoked,	Content PCP	CEN/TR14823	≤ 5 x 10-6n
	Handscraped	Breaking Strength N/mm ²	EN1533	NPD
Width x Length x Thickness	260 x 2800 x 20 mm	Thermal Conductivity	EN12664	0,125 W/mK
Weight per package / per	38 kg / 13.1 kg	Thermal Resistance R-Value	2	.16 (m2K/W)
m2		Biological Durability	EN350-2	Class 1
Area per package	2.9 m ²	CARB2		Compliant
Grading	Dynamic	Slip resistance	CEN/TS15676	NPD
Joint	Tongue & Groove			
Installation method	Glue-down			
Floor heating	No	ist and a water is		
Wear leayer material /	Hardwood / 5 mm			
thickness				
Backside material	Veneer			
Warranty	30 years			

TECHNICAL PROPERTIES

DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. Grande products may continue to develop their rustic nature after the floor has been installed; splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kahrs (UK) Ltd | www.kahrs.com | [©]Kährs, United Kingdom & Ireland 2025-05-13

Kahrs (UK) Ltd | www.kahrs.com | ©Kährs, United Kingdom & Ireland {year}