

ATELIER SMOKED OAK AB 11 MM

Smoked Oak AB, a 2-layer construction, is a clean dark brown floor. Offered with a variety of surface treatments and patterns.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	111PABEKFCKE120	Wood Species	Oak	Moisture	EN13183	7%±2%
EAN Code	7393969042321	Design	1-strip	content	tent	
Surface treatment	Oil This floor should be oiled immediately after installation.	Grading	Calm	Minimun Mean Density kg/m ³ >500 kg/m ³		>500 kg/m ³
		Range	Kährs Master	Reaction To Fire	EN13501-1	Cfl-s1
		Collection	Atelier Collection	Formaldehyde Emission	EN717-1	E1
Design features	Brushed, Microbevelled	Resandable	2 times			
	4-sided	Natural/Stained	Natural	Content PCP	CEN/TR14823	3 ≤ 5 ppm
Dimensions	120 x 1200 mm	Brinell Value	3,7	Breaking	EN1533	NPD
Weight per Package	9.4 kg	Joint	Tongue & Groove	Strength N/mm ²		
Area per Package	1.4 m ²	Floor heating	Yes		5140664	<u> </u>
Package info	Packages may contain start and stop boards.			Thermal Conductivity	EN12664	0,14 W/mK
		Warranty	30 years			
		Wear-layer material	Hardwood	Thermal Resistance R-Value		.08 (m2K/W)
DETAIL DESCRIPTION Normal colour of mainly standing year rings, sapwood not allowed. Small knots up to 5mm allowed. No cracks allowed. COLOUR CHANGE		Wear Layer Thickness	3.5 mm	Biological Durability	EN350-2	Class 1
		Thickness	11 mm	CARB2		Compliant
		Installation method	Glue-down	Slipperiness CEN/TS15676		
		Surface Colour	Dark Brown			

Smoked product - little colour change.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.