



## CASTILLO OAK

The raw umber nuances found in this single-strip oak floor from the Grande Collection add to its extremely rustic character. The beautiful and naturally occurring knots and cracks that pepper the surface are highlighted by the richly smoked finish. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. This product must be oiled after installation and prior to use.

### PRODUCT DETAILS

<b>Article Number</b>	201XDDEKFRKE280
<b>EAN Code</b>	7393969035200
<b>Surface treatment</b>	Oil This floor should be oiled immediately after installation.
<b>Design features</b>	Bevelled 4-sided, Brushed, Smoked
<b>Dimensions</b>	260 x 2800 mm
<b>Weight per Package</b>	38 kg
<b>Area per Package</b>	2.9 m <sup>2</sup>
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. Grande products may continue to develop their rustic nature after the floor has been installed, splits and cracks that occur after installation are normal and should be considered part of the timbers natural character.

### COLOUR CHANGE

Smoked product - noticable color change over time.


### FACTS

<b>Wood Species</b>	Oak
<b>Design</b>	1-strip
<b>Grading</b>	Dynamic
<b>Range</b>	Kährs Supreme
<b>Collection</b>	Grande Collection
<b>Resandable</b>	2-4 times
<b>Natural/Stained</b>	Natural
<b>Joint</b>	Tongue & Groove
<b>Floor heating</b>	No
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear Layer Thickness</b>	5 mm
<b>Backside material</b>	Veneer
<b>Thickness</b>	20 mm
<b>Installation method</b>	Glue-down

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>500 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 ppm
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,125 W/mK
<b>Thermal Resistance R-Value</b>	.16 (m2K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	
<b>Slipperiness</b>	CEN/TS15676	NPD

Other products in this collection



Manor Oak

CERTIFICATES

---



Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*