



XPRESSION GOLDEN OAK

PRODUCT DETAILS

Product type / Construction	Hybrid Flooring / Dry Back LVT
Article Number / EAN Code	101516 / 6418660251627
Design	Tile Design
Width x Length x Thickness	7 x 48 x 1/8"
Weight per package / per m2	35.3 lbs / 8.2 lbs
Area per package / per pallet	46.3 sqft / 3262.5 sqft
Installation method	Glue-Down
Floor heating	Yes

TECHNICAL PROPERTIES

Reaction To Fire	EN13501-1	Cfl-s1
Thermal Resistance R-Value		0.009 (m2K/W)
Residual indentation	EN ISO 24343-1	< 0.05 mm
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R9

TECHNICAL PROPERTIES

Statical electrical propensity	EN 1815	< 2 kV (antistatic)
Effect of castor chair	EN 425	Suitable
Resistance to bacteria and fungi		Good



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs International |
www.kahrs.com | ©Kährs,
USA & Canada 2025-07-01

Other products in this collection



XPRESSION American Cherry



XPRESSION French Walnut



XPRESSION Chestnut



XPRESSION Cool Grey



XPRESSION Smoked



XPRESSION Dark Grey



XPRESSION Almond



XPRESSION Natural



XPRESSION Warm Grey



XPRESSION Dune



XPRESSION Charcoal



XPRESSION Golden Oak



XPRESSION Hazel