



XPRESSION ALMOND

PRODUCT DETAILS TECHNICAL PROPERTIES

Article Number	101511	Reaction To Fire	EN13501-1	Cfl-s1	
Dimensions	177.8 x 1219.2 mm	Thermal Resistance R-Value		0.009 (m2K/W)	(30 p)
Weight per Package	16 kg	Residual indentation	EN ISO	< 0.05 mm	
Area per Package	4.3 m ²		24343-1		
Area per pallet	303.1 m²	Dimensional stability	EN ISO 23999	< 0.1 %	K N W N
FACTS	Dry back Xpression flooring	Colour fastness	EN ISO 105- B02	≥ 6	\$
Design	Wood design	Slip resistance	EN 13893	DS (>0.3)	25
Range	Luxury Tiles	Slip resistance	DIN 51130	R9	
Collection	Xpression PVC-FREE Dry Back Collection	Statical electrical propensity	EN 1815	< 2 kV (antistatic)	7
Floor heating	Yes	Resistance to bacteria	Resistance to bacteria and fungi		
	2 mm				

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.







FACTS TECHNICAL PROPERTIES

Installation method

Glue-down

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.





