

## PURE OAK 2-STRIP

Celebrating the warm and nurturing natural beauty of oak wood, Pure Oak 2-strip is a natural oak floor from the Life Collection. A calm wood collection with few knots and an authentic look and feel. The 2-strip design gives a lifeful impression. An innovative matt lacquer finish eliminates glare while protecting the wood from daily wear.

| PRODUCT DETAILS             |  | TECHNICAL PROPERTIES                |             |                |
|-----------------------------|--|-------------------------------------|-------------|----------------|
| Product type / Construction | Wood Flooring / Veneer floors                | Minimun Mean Density                |             | >800 kg/m³     |
| Article Number / EAN Code   | LTCLRW3003-193 / 7393969107457               | kg/m³                               |             |                |
| Design / Wood Species       | 2-strip / Oak                                | Reaction To Fire                    | EN13501-1   | Cfl-s1         |
| Surface Treatment /         | Matt lacquer / Natural                       | Formaldehyde Emission               | EN717-1     | E1             |
| Natural/Stained             |  | Content PCP                         | CEN/TR14823 | ≤ 5 x 10-6n    |
| Width x Length x Thickness  | 193 x 1225 x 7 mm                            | Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD            |
| Weight per package / per    | 18.03 kg / 6.37 kg                           | Thermal Resistance R-Value          |             | .0533 (m2K/W)  |
| m2                          |  | <b>Biological Durability</b>        | EN350-2     | Class 1        |
| Area per package / per      | 2.832 m <sup>2</sup> / 113.28 m <sup>2</sup> | CARB2                               |             | Compliant      |
| pallet                      |  | Resistance to indentation           |             | >40 Newton/mm2 |
| Grading                     | Calm   |                                     | e.          |                |
| Joint                       | Woodloc® 5G                                  |                                     |             |                |
| Installation method         | Glue-down, Floating                          |                                     |             |                |
| Floor heating               | Yes  |                                     |             |                |
| Wear leayer material /      | Hardwood / 0.6 mm                            |                                     |             |                |
| thickness                   |  |                                     |             |                |
| Core material               | HDF  |                                     |             |                |
| LRV / LRV Std1 / LRV Std2   | 32 / 3.3 / 6.6                               |                                     |             |                |
|                             |  |                                     |             |                |

## DETAILED DESCRIPTION

Moisture content

Even colour with minor variations. Small-sized knots in limited numbers allowed.

EN13183

Colour change: The colour matures over time

Packages may contain start and stop boards.

## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

7%±2%

Kahrs (UK) Ltd | www.kahrs.com | <sup>©</sup>Kährs, United Kingdom & Ireland 2025-08-31

## Other products in this collection







COCONUT CREAM WIDE

LIGHT SUEDE WIDE