

BUTTERSCOTCH 2-STRIP

A warm tone reminiscent of browned sugar and butter. Butterscotch 2-strip is a stained oak floor from the Life Collection. A calm wood collection with few knots and an authentic look and feel. The 2-strip design gives a lifeful impression. An innovative matt lacquer finish eliminates glare while protecting the wood from daily wear.

Product type / ConstructionWood Floors / Veneer floorsMoisture contentEN13183Article Number / EAN CodeLTCLRW3007-193 / 7393969107570Minimun Mean DensityVeneer floorsKg/m³Design / Wood Species2-strip / Oakkg/m³EN13501-1Surface treatment /Matt lacquer / StainedReaction To FireEN13501-1Natural/StainedFormaldehyde EmissionEN717-1Width x Length x Thickness193 x 1225 x 7 mmContent PCPCEN/TR1482Weight per package / per18.03 kg / 6.37 kgBreaking Strength N/mm²EN1533m2Thermal ConductivityEN12664Area per package / per2.832 m² / 113.28 m²Thermal Resistance R-ValuepalletBiological DurabilityEN350-2GradingCalmCARB2JointWoodloc® 5GResistance to indentation	7%±2% >800 kg/m ³ Cfl-s1
Design / Wood Species2-strip / Oakkg/m³Surface treatment /Matt lacquer / StainedReaction To FireEN13501-1Natural/StainedFormaldehyde EmissionEN717-1Width x Length x Thickness193 x 1225 x 7 mmContent PCPCEN/TR1482Weight per package / per18.03 kg / 6.37 kgBreaking Strength N/mm²EN1533m2Thermal ConductivityEN12664Area per package / per2.832 m² / 113.28 m²Thermal Resistance R-ValuepalletBiological DurabilityEN350-2GradingCalmCARB2JointWoodloc® 5GResistance to indentation	
Surface treatment / Natural/StainedMatt lacquer / StainedReaction To FireEN13501-1Natural/StainedFormaldehyde EmissionEN717-1Width x Length x Thickness193 x 1225 x 7 mmContent PCPCEN/TR1482Weight per package / per18.03 kg / 6.37 kgBreaking Strength N/mm²EN1533m2Thermal ConductivityEN12664Area per package / per2.832 m² / 113.28 m²Thermal Resistance R-ValuepalletBiological DurabilityEN350-2GradingCalmCARB2JointWoodloc® 5GResistance to indentation	Cfl-s1
Natural/StainedFormaldehyde EmissionEN717-1Width x Length x Thickness193 x 1225 x 7 mmContent PCPCEN/TR1482Weight per package / per18.03 kg / 6.37 kgBreaking Strength N/mm²EN1533m2Thermal ConductivityEN12664Area per package / per2.832 m² / 113.28 m²Thermal Resistance R-ValuepalletBiological DurabilityEN350-2GradingCalmCARB2JointWoodloc® 5GResistance to indentation	Cfl-s1
Width x Length x Thickness193 x 1225 x 7 mmContent PCPCEN/TR1482Weight per package / per18.03 kg / 6.37 kgBreaking Strength N/mm²EN1533m2Thermal ConductivityEN12664Area per package / per2.832 m² / 113.28 m²Thermal Resistance R-ValuepalletBiological DurabilityEN350-2GradingCalmCARB2JointWoodloc® 5GResistance to indentation	
Weight per package / per 18.03 kg / 6.37 kg Breaking Strength N/mm² EN1533 m2 Thermal Conductivity EN12664 Area per package / per 2.832 m² / 113.28 m² Thermal Resistance R-Value pallet Biological Durability EN350-2 Grading Calm CARB2 Joint Woodloc® 5G Resistance to indentation	E1
m2 Thermal Conductivity EN12664 Area per package / per 2.832 m² / 113.28 m² Thermal Resistance R-Value pallet Biological Durability EN350-2 Grading Calm CARB2 Joint Woodloc® 5G Resistance to indentation	23 ≤ 5 ppm
Area per package / per 2.832 m² / 113.28 m² Thermal Resistance R-Value pallet Biological Durability EN350-2 Grading Calm CARB2 Joint Woodloc® 5G Resistance to indentation	NPD
palletBiological DurabilityEN350-2GradingCalmCARB2JointWoodloc® 5GResistance to indentation	0,13W/mK
Grading Calm CARB2 Joint Woodloc® 5G Resistance to indentation	.0533 (m2K/W)
Joint Woodloc® 5G Resistance to indentation	Class 1
	Compliant
	>40 Newton/mm2
Installation method Glue-down, Floating	
Floor heating Yes	B BYGEVARU BEDOMNINGEN
Wear leayer material / Hardwood / 0.6 mm BASTA	
thickness	
Resandable Not resandable	((
Core material HDF	
LRV / LRV Std1 / LRV Std2 29 / 1.8 / 3.6	
Warranty 15 years	

DETAILED DESCRIPTION

Even colour with minor variations.

Small sized knots in limited numbers allowed.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



www.kahrs.com | [©]Kährs {year}





COCONUT CREAM WIDE

LIGHT SUEDE WIDE