



## PURE WALNUT 2-STRIP

Capturing the warmth and richness of walnut, Pure walnut 2-strip is a natural walnut floor from the Life Collection. A calm wood collection with few knots and an authentic look and feel. The 2-strip design gives a lifeful impression. An innovative matt lacquer finish eliminates glare while protecting the wood from daily wear.

| PRODUCT DETAILS  |   | FACTS                     |                     | TECHNICAL PROPERTIES                        |             |                |
|--|---|---------------------------|---------------------|---|-------------|----------------|
| Article Number   | LTCLRW3010-193                              | Wood Species              | Walnut              | Moisture                                    | EN13183     | 7%±2%          |
| EAN Code   | 7393969107631                               | Design                    | 2-strip             | content                                     |             |                |
| Surface Treatment  | Matt lacquer                                | Grading                   | Calm                | Minimun Mean Density kg/m³ >800 kg/m³       |             |                |
| Dimensions   | 193 x 1225 mm                               | Range                     | Kährs Life          | Reaction To<br>Fire                         | EN13501-1   | Cfl-s1         |
| Weight per Package   | 18.03 kg                                    | Collection                | Life Collection     | Formaldehyde                                | EN717-1     | E1             |
| Area per Package   | 2.832 m <sup>2</sup>                        | Natural/Stained           | Natural             | Emission                                    |             |                |
| Area per pallet  | 113.28 m <sup>2</sup>                       | Joint                     | Woodloc® 5G         | Content PCP                                 | CEN/TR14823 | ≤ 5 x 10-6n    |
| Package info   | Packages may contain start and stop boards. | Floor heating             | Yes                 | Breaking                                    | EN1533      | NPD            |
|  |   |                           | 15 years            | <ul> <li>Strength</li> <li>N/mm²</li> </ul> |             |                |
| DETAIL DESCRIPTION   |   | Wear-layer material       | Hardwood            | Thermal                                     | EN12664     | 0.134 W/mK     |
| Even colour with minor variations. Small-sized knots in limited numbers allowed. |   | Wear Layer Thickness      | 0.6 mm              | Conductivity                                |             |                |
|  |   | Core material             | HDF                 | Thermal Resistance R-Value                  |             | .0533 (m2K/W)  |
| COLOUR CHANGE  |   |                           | 7 mm                | Biological<br>Durability                    | EN350-2     | Class 1        |
| The colour matures over time   |   | Installation method       | Glue-down, Floating | CARB2                                       |             | Compliant      |
|  |   | Resistance to indentation | >40 Newton/mm2      | Resistance to indentation                   |             | >40 Newton/mm2 |

## Other products in this collection

Earl Grey Wide



Driftwood Wide B GUSTAF KÄHR www தெருந்திரும் | © Kährs 2023 ure Oak Wide





Coconut Cream Wide

Light Suede Wide

## CERTIFICATES









## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.