



## OAK CRAYON

This single-strip, stained oak floor from the Lux Collection features a warm grey stain with subtle earth tones, complemented by an ultra-matt lacquer finish. Four-sided micro-bevelling at the edging ensures a classic fullplank look and feel. Each board is carefully brushed to perfection to enhance the natural character of the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

| PRODUCT DETAILS             |   |  |
|-----------------------------|---|--|
| Product type / Construction | Wood Flooring / 3-layer parquet             |  |
| Article Number / EAN Code   | 151N51EKL4KW240 / 7393969048149             |  |
| Design / Wood Species       | 1-strip / Oak                               |  |
| Surface treatment /         | Ultra matt lacquer / Stained                |  |
| Natural/Stained             |   |  |
| Design features             | Microbevelled 4-sided, Brushed              |  |
| Width x Length x Thickness  | 151 x 2420 x 15 mm                          |  |
| Weight per package / per    | 17.85 kg / 8.15 kg                          |  |
| m2                          |   |  |
| Area per package / per      | 2.19 m <sup>2</sup> / 118.26 m <sup>2</sup> |  |
| pallet                      |   |  |
| Grading                     | Lively                                      |  |
| Joint                       | Woodloc® 5S                                 |  |
| Installation method         | Floating, Glue-down                         |  |
| Floor heating               | Yes   |  |
| Wear leayer material /      | Hardwood / 3.5 mm                           |  |
| thickness                   |   |  |
| Resandable                  | 2-3 times                                   |  |
| Core material               | Pine/Spruce/Alder                           |  |
| Brinell value / range       | 3,7 / 2.2 - 5.9                             |  |

| LRV / LRV Std1             | 31.5 / 1.9  |             |
|----------------------------|-------------|-------------|
| Warranty                   | 30 years    |             |
| TECHNICAL PROPERTIES       |             |             |
| Moisture content           | EN13183     | 7%±2%       |
| Minimun Mean Density       |             | >500 kg/m³  |
| kg/m³                      |             |             |
| Reaction To Fire           | EN13501-1   | Dfl-s1      |
| Formaldehyde Emission      | EN717-1     | E1          |
| Content PCP                | CEN/TR14823 | ≤ 5 ppm     |
| Breaking Strength N/mm²    | EN1533      | NPD         |
| Thermal Conductivity       | EN12664     | 0,14 W/mK   |
| Thermal Resistance R-Value | !           | .11 (m2K/W) |
| Biological Durability      | EN350-2     | Class 1     |
| CARB2                      |             | Compliant   |
| Slip resistance            | CEN/TS15676 | NPD         |



















## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots, fillings and cracks. Knots, fillings and cracks will be present in all sizes and numbers.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Stained product - noticeable color change over time

Packages may contain start and stop boards.

Descriptions & Imagery All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items

described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot

## Other products in this collection

Oak Coast

Oak Shore



Oak Sun

Oak Terra