



## OAK HENNA

This plank oak floor from the Canvas Collection features a warm, mid-tone brown stain with soft white graining and neutral undertones. With subtle variation and some knots to provide dimension, the result is a fresh take on a classic brown color. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The matte finish eliminates glare while protecting the wood from daily wear. Four-sided micro-bevelling at the edges ensures a classic full plank look and feel.

| PRODUCT DETAILS    |   | FACTS                |                     | TECHNICAL PROPERTIES  |             |             |
|--------------------|---|----------------------|---------------------|---|-------------|-------------|
| Article Number     | 13106AEK1NKW185                             | Wood Species         | White Oak           | Moisture content  | EN13183     | 7%±2%       |
| EAN Code           | 7393969048033                               | Design               | 1-strip             | Minimum Mean Density kg/m <sup>3</sup> >500 kg/m <sup>3</sup> |             |             |
| Surface Treatment  | Matte finish                                | Grading              | Lively              | Reaction To Fire  | EN13501-1   | Dfl-s1      |
| Refining Treatment | Microbeveled 4-sided, Brushed               | Range                | Kährs Avanti        | Formaldehyde Emission   | EN717-1     | E1          |
| Dimensions         | 5 x 73 1/4 "                                | Collection           | Canvas Collection   | Content PCP   | CEN/TR14823 | ≤ 5 x 10-6n |
| Weight per Package | 28 lbs                                      | Resandable           | 2 times             | Breaking Strength N/mm <sup>2</sup>                           | EN1533      | NPD         |
| Area per Package   | 17.8 sqft                                   | Natural/Stained      | Stained             | Thermal Conductivity  | EN12664     | 0,08 W/mK   |
| Area per pallet    | 1120.3 sqft                                 | Brinell Value        | 3,7                 | Thermal Resistance R-Value                                    |             | .15 (m2K/W) |
| Package info       | Packages may contain start and stop boards. | Joint                | Woodloc® 5G         | Biological Durability   | EN350-2     | Class 1     |
| DETAIL DESCRIPTION |   | Floor heating        | Yes                 | CARB2   |             | Compliant   |
|                    |   | Warranty             | 25 years            | Slipperiness  | CEN/TS15676 | NPD         |
|                    |   | Warranty             | 25 years            |   |             |             |
|                    |   | Wear-layer material  | Hardwood            |   |             |             |
|                    |   | Wear Layer Thickness | 1/8"                |   |             |             |
| COLOR CHANGE       |   | Core material        | Pine/Spruce lamella |   |             |             |
|                    |   | Thickness            | 1/2"                |   |             |             |
|                    |   | Installation method  | Floating, Glue-Down |   |             |             |
|                    |   | Surface Color        | Brown               |   |             |             |

Other products in this collection



Oak Fawn



Oak Henna



Oak Heather



Oak Cadence



Oak Pratica



Oak Reiter



Oak Morel



Oak Muse



Oak Tapa



Oak Curio



Oak Carbon



Oak Etch



Oak Tuft



Oak Mostra

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.