



OAK STARNBERG

Oak Starnberg is a very rustic and naturally toned product. Dark filled and partly filled cracks and knots is a common feature.

PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	151N9AEKF0KW240 / 7393969033091
Design / Wood Species	Plank / Oak
Surface treatment /	Oil / Natural
Natural/Stained	
Design features	Microbevelled 4-sided, Brushed
Width x Length x Thickness	187 x 2420 x 15 mm
Weight per package / per	24 kg / 8.89 kg
m2	
Area per package / per	2.72 m ² / 122.4 m ²
pallet	
Grading	Dynamic
Joint	Woodloc® 5S
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 3 mm
thickness	
Resandable	2-3 times
Core material	Pine/Spruce
Hardness (Brinell) value /	3,7 / 2.2 - 5.9
range	

PRODU	CTL	DETAI	LS

LRV / LRV Std1 / LRV Std2	39 / 3.6 / 7.2	
Warranty	20 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD













DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Other products in this collection

