

## OAK STARNBERG

Oak Starnberg is a very rustic and naturally toned product. Dark filled and partly filled cracks and knots is a common feature.

| PRODUCT DETAILS             |                                 | PRODUCT DETAILS                     |                             |                        |
|-----------------------------|---------------------------------|-------------------------------------|-----------------------------|------------------------|
| Product type / Construction | Wood Floors / 3-layer parquet   | Warranty                            | 20 years                    |                        |
| Article Number / EAN Code   | 151N9AEKF0KW240 / 7393969033091 | TECHNICAL PROPERTIES                |                             |                        |
| Design / Wood Species       | 1-strip / Oak                   | Moisture content                    | FN13183                     | 7%±2%                  |
| Surface treatment /         | Oil / Natural                   |                                     | LINISIOS                    | >500 kg/m <sup>3</sup> |
| Natural/Stained             |                                 | Minimun Mean Density                |                             | ~500 kg/11             |
| Design features             | Microbevelled 4-sided, Brushed  |                                     | EN13501-1                   | Dfl-s1                 |
| Width x Length x Thickness  | 187 x 2420 x 15 mm              | — Formaldehyde Emission             | EN717-1                     | E1                     |
| Weight per package / per    | 24 kg / 8.89 kg                 |                                     | CFN/TR14823                 | ≤ 5 ppm                |
| m2                          |                                 | Breaking Strength N/mm <sup>2</sup> | EN1533                      | NPD                    |
| Area per package            | 2.7 m <sup>2</sup>              | — Thermal Conductivity              | EN12664                     | 0,11W/mK               |
| Grading                     | Dynamic                         | — Thermal Resistance R-Value        |                             | .11 (m2K/W)            |
| Joint                       | Woodloc® 5S                     |                                     | EN350-2                     | · · · · ·              |
| Installation method         | Floating, Glue-down             | Biological Durability               | EIN350-2                    | Class 1                |
| Floor heating               | Yes                             | CARB2                               |                             | Compliant              |
| Wear leayer material /      | Hardwood / 3 mm                 | Slip resistance                     | CEN/TS15676                 | NPD                    |
| thickness                   |                                 | SCHWAN ECS                          | (MISSONI GANI LANI INTERLAT | "                      |
| Resandable                  | 2-3 times                       |                                     |                             |                        |
| Core material               | Pine/Spruce lamella             | SundaHus SundaHus                   | ΔΑΣΙΑ                       |                        |
| Hardness (Brinell) value /  | 3,7 / 2.2 - 5.9                 |                                     |                             |                        |
| range                       |                                 |                                     |                             |                        |

## DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

**Oil:** This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

## **Descriptions & Imagery**

www.kahrs.com | <sup>©</sup>Kährs 2025-06-27

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## Other products in this collection



OAK VERONA MATT



OAK ROCHFORD



OAK HAMPSHIRE

OAK SIENA SATIN



OAK BURGUNDY





OAK ARDENNE



OAK VERONA ULTRA MATT





OAK SIENA MATT



OAK COMO