



OAK SUPAI

Oak Supai is a 3-strip floor with moderate color variations and a dark brown stain. May contain minor knots.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	133NABEK5LUW240	Wood Species	White Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969034135	Design	3-strip	Minimum Mean Density kg/m³ >500 kg/m³		
Surface Treatment	Silk matte finish	Range	Kährs Avanti	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	7 7/8 x 95 3/8 "	Collection	Tres collection	Formaldehyde Emission	EN717-1	E1
Weight per Package	54 lbs	Resandable	2 times	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	36.6 sqft	Natural/Stained	Stained	Breaking Strength N/mm²	EN1533	NPD
Area per pallet	1829.9 sqft	Brinell Value	3,7	Thermal Conductivity	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Joint	Woodloc® 5G	Thermal Resistance R-Value	.09 (m2K/W)	
DETAIL DESCRIPTION		Floor heating	Yes	Biological Durability	EN350-2	Class 1
		Warranty	20 years	CARB2	Compliant	
		Warranty	20 years	Slipperiness	CEN/TS15676	NPD
		Wear-layer material	Hardwood			
		Wear Layer Thickness	1/8"			
COLOR CHANGE		Core material	Pine/Spruce lamella			
		Thickness	1/2"			
		Installation method	Floating, Glue-Down			
Stained product - noticable color change over time.						

Other products in this collection



European Maple Gotha



Red Oak Nature



Ash Ceriale



Ash Vaila



Oak Bisbee



Oak Supai



Oak Pima



Oak Lecco

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.