



7%±2%  $>500 \text{ kg/m}^3$ 

Dfl-s1 E1

NPD

≤ 5 x 10-6n NPD 0,14 W/mK .09 (m2K/W) Class 1 Compliant

## OAK BISBEE

Oak Bisbee is a 3-strip floor with moderate color variations and a brown stain. May contain minor knots.

PRODUCT DETAILS		TECHNICAL PROPERTIES	
Construction	3-layer engineered	Moisture content	EN13183
Article Number / EAN Code	133NABEK5MUW240 / 7393969034180	Minimun Mean Density	
Design / Wood Species	3-strip / White Oak	kg/m³	
Surface Treatment /	Silk matte finish / Stained	Reaction To Fire	EN13501-1
Natural/Stained		Formaldehyde Emission	EN717-1
Width x Length x Thickness	7 7/8 x 95 3/8 x 1/2"	Content PCP	CEN/TR14823
Weight per package / per	54 lbs / 15.9 lbs	Breaking Strength N/mm <sup>2</sup>	EN1533
m2		Thermal Conductivity	EN12664
Area per package	36.6 sqft	Thermal Resistance R-Value	
Joint	Woodloc® 5G	Biological Durability	EN350-2
Installation method	Floating, Glue-Down	CARB2	
Floor heating	Yes	Slip resistance	CEN/TS15676
Wear leayer material /	Hardwood / 1/8"	and and an analysis	
thickness		TSCA floor	) ( <b>C</b>
Resandable	2 times	CARB P2	
Core material	Pine/Spruce lamella		



## **TECHNICAL PROPERTIES**

## DETAILED DESCRIPTION

Brinell value / range

Warranty

Naturally occuring wood colour variations allowed, from light to dark brown.

3,7 / 2.2 - 5.9

20 years

The product includes medium sound and black knots. Knots may vary in size and numbers.

**Colour change**: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## Other products in this collection



European Maple Gotha



Red Oak Nature



Ash Ceriale



Ash Vaila



Oak Bisbee

Oak Supai

Oak Lecco

Oak Pima