



OAK PIMA

Golden brown highlights mix with sandstone hues in this stained, 3-strip oak floor from the Tres collection resulting in a warm and classic expression. The silk lacquer finish adds lustre, giving the floor a polished appearance while protecting the wood from daily wear.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	133NABEK7CUW240	Wood Species	Oak	Moisture	EN13183	7%±2%
EAN Code	7393969034173	Design	3-strip	content		
Surface treatment	High gloss lacquer	Range	Kährs Avanti	Minimun Mean Density kg/m³ >500 kg/m³		
Dimensions	200 x 2423 mm	Collection	Tres collection	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	24.5 kg	Resandable	2-3 times	Formaldehyde Emission	EN717-1	E1
Area per Package	3.4 m ²	Natural/Stained	Stained			
Package info	Packages may contain start and stop boards.	Brinell Value	3,7	Content PCP	CEN/TR14823	≤ 5 ppm
		Joint	Woodloc® 5G	Breaking Strength N/mm ²	EN1533	NPD
		Floor heating	Yes			
		Warranty	20 years	Thermal EN12664 Conductivity	EN12664	0,14 W/mK
		Warranty US	20 years			
		Wear-layer material	Hardwood	Thermal Resistance R-Value		.09 (m2K/W)
		Wear Layer Thickness	2.6 mm	Biological Durability	EN350-2	Class 1
		Core material	Pine/Spruce lamella	CARB2		Compliant
		Thickness	13 mm		CEN/TS15676	'
		Installation method	Floating, Glue-down			
		Surface Colour	Light brown 7C			

Other products in this collection



CERTIFICATES

Oak Pima









Oak Erve

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Oak Abetone

Oak Lecco