



## OAK PIMA

Oak Pima is a 3-strip floor with moderate color variations and a light brown highgloss stain. May contain minor knots.

### PRODUCT DETAILS

<b>Article Number</b>	133NABEK7CUW 0
<b>EAN Code</b>	7393969034173
<b>Surface Treatment</b>	High gloss finish
<b>Dimensions</b>	95 3/8 x 7 7/8 x 1/2"
<b>Weight per Package</b>	54 lbs
<b>Area per Package</b>	3.4
<b>AreaPerPalletM2</b>	0
<b>Package info</b>	Packages may contain start and stop boards.

### FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	3-strip
<b>Range</b>	Kährs Avanti
<b>Collection</b>	Tres Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5G
<b>Floor heating</b>	Yes
<b>Warranty</b>	20 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	7/64"
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness</b>	1/2"
<b>Installation method</b>	Floating, Glue-Down

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m³</b>	>500 kg/m³	
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10-6n
<b>Breaking Strength N/mm²</b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>	.09 (m2K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	



### **Descriptions & Imagery**

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*