



# OAK ABETONE

Oak Abetone is a 3-strip floor with moderate colour variations and a white stain. May contain minor knots.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	133NABEK1VKW240	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969034142	Design	3-strip	Minimum Mean Density kg/m³ >500 kg/m³		
Surface Treatment	Matt lacquer	Range	Kährs Avanti	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	200 x 2423 mm	Collection	Tres collection	Formaldehyde Emission	EN717-1	E1
Weight per Package	24.5 kg	Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	3.4 m²	Brinell Value	3,7	Breaking Strength N/mm²	EN1533	NPD
Area per pallet	170 m²	Joint	Woodloc® 5G	Thermal Conductivity	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Floor heating	Yes	Thermal Resistance R-Value	.09 (m2K/W)	
DETAIL DESCRIPTION			20 years	Biological Durability	EN350-2	Class 1
		Wear-layer material	Hardwood	CARB2	Compliant	
		Wear Layer Thickness	2.6 mm	Slipperiness	CEN/TS15676	NPD
COLOUR CHANGE		Core material	Pine/Spruce/Alder			
			13 mm			
		Installation method	Floating, Glue-down			
		Stained product - noticable color change over time.				

Other products in this collection



European Maple Gotha



Ash Ceriale



Ash Vaila



Oak Erve



Oak Abetone



Oak Lecco

CERTIFICATES



Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*