



OAK ERVE OILED

The fawn brown and earthy tones found in this 3-strip oak floor from the Tres Collection are dotted with darker knots for a lively and rustic expression.

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Product type / Construction	Wood Floors / 3-layer parquet	Moisture content	EN13183	7%±2%
Article Number / EAN Code	133NCDEKF0KW240 / 7393969034258	Minimum Mean Density		>500 kg/m³
Design / Wood Species	3-strip / Oak	kg/m³		
Surface treatment / Natural/Stained	Oil / Natural	Reaction To Fire	EN13501-1	Dfl-s1
Width x Length x Thickness	200 x 2423 x 13 mm	Formaldehyde Emission	EN717-1	E1
Weight per package / per m2	24.5 kg / 7.21 kg	Content PCP	CEN/TR14823	≤ 5 ppm
Area per package / per pallet	3.4 m² / 170 m²	Breaking Strength N/mm²	EN1533	NPD
Grading	Lively	Thermal Conductivity	EN12664	0,11W/mK
Joint	Woodloc® 5G	Biological Durability	EN350-2	Class 1
Installation method	Floating, Glue-down	CARB2		Compliant
Floor heating	Yes	Slip resistance	CEN/TS15676	NPD
Wear leayer material / thickness	Hardwood / 2.6 mm			
Resandable	2-3 times			
Core material	Pine/Spruce/Alder			
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9			
Warranty	20 years			



DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes medium sound and black knots. Knots may vary in size and numbers.

- Oil:** This floor should be oiled immediately after installation.
- Colour change:** Some muting of colour variation to medium, straw brown.
- Packages may contain start and stop boards.

Other products in this collection



OAK LECCO MATT



OAK LECCO OILED



OAK LECCO ULTRA MATT



OAK ABETONE MATT



OAK ERVE MATT



OAK CORTINA



OAK VANILLA



ASH POLAR 3S 5G



OAK REALBA MATT 226



EUROPEAN MAPLE GOTHA



RED OAK NATURE



ASH CERIALE



ASH VAILA



OAK BISBEE



OAK SUPAI



OAK PIMA



OAK ERVE OILED



OAK LECCO SATIN