



## OAK ERVE OILED

The fawn brown and earthy tones found in this 3-strip oak floor from the Tres Collection are dotted with darker knots for a lively and rustic expression.

PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	
Article Number / EAN Code	133NCDEKF0KW240 / 7393969034258	
Design / Wood Species	3-strip / Oak	
Surface treatment /	Oil / Natural	
Natural/Stained		
Width x Length x Thickness	200 x 2423 x 13 mm	
Weight per package / per	24.5 kg / 7.21 kg	
m2		
Area per package	3.4 m <sup>2</sup>	
Grading	Lively	
Joint	Woodloc® 5G	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 2.6 mm	
thickness		
Resandable	2-3 times	
Core material	Pine/Spruce/Alder	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	20 years	

## **TECHNICAL PROPERTIES**

Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Resistance R-Value		.09 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

















## DETAILED DESCRIPTION


Naturally occuring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes medium sound and black knots. Knots may vary in size and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

## Other products in this collection





OAK LECCO SATIN