



# REEF OAK

The natural shades of this oak single-strip floor in the Unity Collection, range from subtle tawny to sunset umbers and chocolate browns with just a few scattered knots. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

## PRODUCT DETAILS

|                                     |                                 |
|-------------------------------------|---------------------------------|
| Product type / Construction         | Wood Floors / Veneer floors     |
| Article Number / EAN Code           | 101P3AEK09KW120 / 7393969030601 |
| Design / Wood Species               | 1-strip / Oak                   |
| Surface treatment / Natural/Stained | Matt lacquer / Natural          |
| Design features                     | Bevelled 4-sided, Brushed       |
| Width x Length x Thickness          | 125 x 1200 x 10 mm              |
| Weight per package / per m2         | 14 kg / 9.33 kg                 |
| Area per package                    | 1.5 m <sup>2</sup>              |
| Grading                             | Variation                       |
| Joint                               | Woodloc®                        |
| Installation method                 | Floating, Glue-down             |
| Floor heating                       | Yes                             |
| Wear leayer material / thickness    | Hardwood / 1.9 mm               |
| Resandable                          | 1 time                          |
| Core material                       | HDF                             |
| Backside material                   | Veneer                          |

## PRODUCT DETAILS

|                                  |                 |
|----------------------------------|-----------------|
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |
| Warranty                         | 20 years        |

## TECHNICAL PROPERTIES

|  |             |                        |
|--|-------------|------------------------|
| Moisture content                       | EN13183     | 7%±2%                  |
| Minimum Mean Density kg/m <sup>3</sup> |             | >800 kg/m <sup>3</sup> |
| Reaction To Fire                       | EN13501-1   | Cfl-s1                 |
| Formaldehyde Emission                  | EN717-1     | E1                     |
| Content PCP                            | CEN/TR14823 | ≤ 5 ppm                |
| Breaking Strength N/mm <sup>2</sup>    | EN1533      | NPD                    |
| Thermal Conductivity                   | EN12664     | 0,14 W/mK              |
| Thermal Resistance R-Value             |             | .07 (m2K/W)            |
| Biological Durability                  | EN350-2     | Class 1                |
| CARB2                                  |             | Compliant              |
| Slip resistance                        | CEN/TS15676 | NPD                    |

## DETAILED DESCRIPTION

Even colour with minor variations.

Small sized knots in limited numbers allowed.

**Colour change:** Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.



## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



ORCHARD WALNUT



GARDEN WALNUT



ARCTIC OAK