



REEF OAK

Reef oak is a natural one strip design. May contain small knots and mild color variation.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	101P3AEK09KW120	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969030601	Design	1-strip	Minimum Mean Density kg/m³ >800 kg/m³		
Surface Treatment	Matt lacquer	Grading	Variation	Reaction To Fire	EN13501-1	Cfl-s1
Refining Treatment	Bevelled 4-sided, Brushed	Range	Kährs Spirit	Formaldehyde Emission	EN717-1	E1
Dimensions	125 x 1200 mm	Collection	Unity Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Weight per Package	14 kg	Natural/Stained	Natural	Breaking Strength N/mm²	EN1533	NPD
Area per Package	1.5 m²	Brinell Value	3,7	Thermal Conductivity	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Joint	Woodloc®	Thermal Resistance R-Value	.07 (m2K/W)	
DETAIL DESCRIPTION		Floor heating	Yes	Biological Durability	EN350-2	Class 1
Even colour with minor variations. Small sized knots in limited numbers allowed.			20 years	CARB2	Compliant	
		Wear-layer material	Hardwood	Slipperiness	CEN/TS15676	NPD
		Wear Layer Thickness	1.9 mm			
COLOUR CHANGE		Core material	HDF			
Some muting of colour variation to medium, straw brown.		Backside material	Veneer			
			10 mm			
		Installation method	Floating, Glue-down			

Other products in this collection



Reef Oak



Park Oak



Orchard Walnut



Garden Walnut



Arctic Oak

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.