



REEF OAK

Reef oak is a natural one strip design. May contain small knots and mild color variation.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	101P3AEK09KW120	Wood Species	White Oak	Moisture	EN13183	7%±2%
EAN Code	7393969030601	Design	1-strip	content		
Surface Treatment	Matte finish	Grading	Variation	Minimun Mean Density kg/m³ >800 kg/m³		
Refining Treatment	Beveled 4-sided, Brushed	Range	Kährs Spirit	Reaction To Fire	EN13501-1	Cfl-s1
Dimensions	4 7/8 x 47 1/4 "	Collection	Unity Collection	Formaldehyde Emission	EN717-1	E1
Weight per Package	30.9 lbs	Resandable	1 time			
Area per Package	16.1 sqft	Natural/Stained	Natural	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Package info	Packages may contain start and stop boards.	Brinell Value	3,7	Breaking Strength N/mm²	EN1533	NPD
		Joint	Woodloc®			
DETAIL DESCRIPTION		Floor heating	Yes	Thermal	EN12664	0,14 W/mK
Even colour with minor variations. Small sized knots in limited numbers allowed. COLOR CHANGE		Warranty	20 years	Conductivity	Conductivity	
		Warranty	20 years	Thermal Resistance R-Value		.07 (m2K/W)
		Wear-layer material	Hardwood	Biological Durability	EN350-2	Class 1
		Wear Layer Thickness	1/8"	CARB2		Compliant
Some muting of colour variation to medium, straw brown.		Core material	HDF	Slipperiness CEN/TS15676		
		Backside material	Veneer	Silpperilless	CEIW/13130/0	D NPD
		Thickness	3/8"			
		Installation method	Floating, Glue-Down			

CERTIFICATES







Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.