



OAK DOME

Oak Dome is a stained oak floor in a warm white tone. The length of the board enhances the depth of the floor.

PRODUCT DETAILS

Product type / Construction	Wood Flooring / Veneer floors
Article Number / EAN Code	37101AEKC1KW180 / 7393969106689
Design / Wood Species	1-strip / Oak
Surface Treatment / Natural/Stained	Matt lacquer / Stained
Refining Treatment	Brushed, Microbevelled 4-sided
Width x Length x Thickness	150 x 1810 x 7 mm
Weight per package / per m2	20 kg / 6.06 kg
Area per package / per pallet	3.26 m ² / 176 m ²
Grading	Calm
Joint	Woodloc®
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 0.6 mm
Core material	HDF
Hardness (Brinell) value / range	5 - 6 / 5 - 6

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density		>800 kg/m ³
Reaction To Fire	EN13501-1	Cfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,22 W/mK
Thermal Resistance R-Value		.031 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



TECHNICAL PROPERTIES

DETAILED DESCRIPTION

Even colour with minor variations.
Small sized knots in limited numbers allowed.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs (UK) Ltd |
www.kahrs.com | ©Kährs,
United Kingdom & Ireland
2026-05-21

