



WALNUT RAIN

Walnut Rain is a flamey grade with colour variation and sap wood, contains knots.

PRODUCT DETAILS

Product type / Construction	Wood Flooring / Veneer floors
Article Number / EAN Code	372085VAF0KW 0 / 7393969105927
Design / Wood Species	2-strip / Walnut
Surface Treatment / Natural/Stained	Oil / Natural
Width x Length x Thickness	193 x 1225 x 7 mm
Weight per package / per m2	20 kg / 7.14 kg
Area per package	2.8 m ²
Grading	Lively
Joint	Woodloc®
Installation method	Glue-down, Floating
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 0.6 mm
Core material	HDF
Hardness (Brinell) value / range	5 - 6 / 5 - 6

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
------------------	---------	-------

TECHNICAL PROPERTIES

Minimun Mean Density	>800 kg/m ³	
kg/m ³		
Reaction To Fire	EN13501-1	Cfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,22 W/mK
Thermal Resistance R-Value	.031 (m2K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

Even colour with minor variations. Sapwood may occur.
Small sized knots in limited numbers allowed.

Oil: This floor should be oiled immediately after installation.

Colour change: Changes to golden brown.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs (UK) Ltd |
www.kahrs.com | ©Kährs,
United Kingdom & Ireland
2025-09-05

