



Accessories / Installation / **Installation**

KÄHRS UNDERLAYER FOAM 2 MM

Underlayer for reduction of step, drum and airborne sound. This underlayer works well over floor heating systems.

Underlayer for reduction of step, drum and airborne sound. This underlayer works well over floor heating systems.

Product details

- Polyethylene foam with closed cells and fine cell structure for high compression strength and Impact Sound Improvement
- Ideal for floating parquet and laminate flooring
- Light, strong and flexible
- Makes the floor more comfortable to walk on
- Suitable in connection with the floor heating systems
- Age resistance > 50 years
- 100% recyclable
- Material: Polyethylene
- Type of format: roll
- Thickness: 2 mm
- Density: 30 kg/m³
- Impact Sound IS: 15 - 19 Db
- Compressive strength CS: 22,7 kPa
- Compressive creep CC: 2,4 kPa
- Punctual conformability PC: 1,5 mm
- Thermal resistance TR: 0,045 m²K/W
- Water vapor resistance SD: 10,9 m

Article Number	710150
Name	KÄHRS UNDERLAYER FOAM 2 MM
EAN Code	7393969239677
Accessory type	Installation
Length	30000 mm
Width	1000 mm
Thickness	2 mm

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.