



OAK SMOKE

The tobacco brown hues prominent in this 3-strip oak floor from the Harmony Collection are enhanced by its richly smoked finish. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

| PRODUCT DETAILS | | |
|-----------------------------|--------------------------------|--|
| Product type / Construction | Wood Floors / 3-layer parquet | |
| Article Number / EAN Code | 153N3EEKF0KW 0 / 7393969033923 | |
| Design / Wood Species | 3-strip / Oak | |
| Surface treatment / | Oil / Natural | |
| Natural/Stained | | |
| Design features | Brushed, Smoked | |
| Width x Length x Thickness | 200 x 2423 x 15 mm | |
| Weight per package / per | 23 kg / 7.93 kg | |
| m2 | | |
| Area per package | 2.9 m ² | |
| Grading | Variation | |
| Joint | Woodloc® 5S | |
| Installation method | Floating, Glue-down | |
| Floor heating | Yes | |
| Wear leayer material / | Hardwood / 3.5 mm | |
| thickness | | |
| Resandable | 2-3 times | |
| Core material | Pine/Spruce lamella | |
| Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 | |
| range | | |

| PRODUCT DETAILS |
|-----------------|
|-----------------|

| Warranty | 30 years | |
|-------------------------------------|-------------|-------------|
| TECHNICAL PROPERTIES | | |
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m³ |
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,11W/mK |
| Thermal Resistance R-Value | ! | .11 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



















DETAILED DESCRIPTION

Even colour with minor variations. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark.

Small sized knots in limited numbers allowed.

 $\begin{tabular}{ll} \textbf{Oil:} This floor should be oiled immediately after installation. \\ \end{tabular}$

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection

