



Accessories / Installation / **Installation**

## COMBIFOAM 2 MM

Sound impact reducing underlay foam, including moisture barrier, ideal for floating installation of wood floors.

Sound impact reducing underlay foam, including moisture barrier, ideal for floating installation of wood floors.

Polyethylene foam with closed cells and fine cell structure for high Compression Strength and Impact Sound Improvement

Polyethylene film moisture barrier with overlap

Evens out irregularities in the subfloor

Makes the floor more comfortable to walk on

Suitable in connection with floor heating

Age resistance > 50 years

100% recyclable

Smell and dust free

Extremely fine surface structure

Can be used for installation on sub floor with RH up to 90%.

Installation: To be installed with the Polyethylene film against the subfloor and using the PE-film overlap of 200 mm between each row of underlay

Density: 30 kg/m<sup>3</sup> (foam)

### Product details

- 
- 

Article Number	710383
Name	COMBIFOAM 2 MM
EAN Code	7393969236492
Accessory type	Installation
Length	15000 mm
Width	1000 mm
Thickness	2 mm

## **Descriptions & Imagery**

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*