



OAK SOIL

The Harmony floors enhance the sensation of your habitat. Combined with the floor's distinctive wood texture, the deep brown nature oil patina breaths history and elegance.

PRODUCT DETAILS

| | |
|---------------------------|---|
| Article Number | 153N6EEKFEKW240 |
| EAN Code | 7393969032711 |
| Surface Treatment | Oil This floor should be oiled immediately after installation. |
| Refining Treatment | Brushed, Light smoked |
| Dimensions | 200 x 2423 mm |
| Weight per Package | 23 kg |
| Area per Package | 2.9 m ² |
| Area per pallet | 130.1 m ² |
| Package info | Packages may contain start and stop boards. |

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Stained product - noticable color change over time.

FACTS

| | |
|-----------------------------|---------------------|
| Wood Species | Oak |
| Design | 3-strip |
| Grading | Lively |
| Range | Kährs Original |
| Collection | Harmony Collection |
| Natural/Stained | Stained |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5S |
| Floor heating | Yes |
| Wear-layer material | Hardwood |
| Wear Layer Thickness | 3.5 mm |
| Core material | Pine/Spruce lamella |
| Installation method | Floating, Glue-down |
| Surface Colour | Brown |


TECHNICAL PROPERTIES

| | | |
|--|--------------------------|--------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10 ⁻⁶ n |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | .11 (m ² K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |
| Slipperiness | CEN/TS15676 | NPD |

Other products in this collection



Oak Shell




Brownie



Alloy



Pale



Ale



Oak Dew



Oak Soil



Oak Stone



Oak Limestone



Oak Lava

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.